



Industrial Portable Utility Heater PKB Series



Model Code:

PKB	20	10	-1
A	B	C	D
A: Series			
B: 12 - 120V, 24 - 240V			
48 - 480V			
C: Watts (1500)			



- Long life spiral finned heating elements
- Long life unit bearing motor
- Durable 20-gauge steel enclosure
- High visibility safety yellow
- Built-in thermostat (40°-100°F)
- Fan only switch
- 6ft. SO cord (no plug)
- Dual carrying handles
- Cord storage feature
- Heavy duty 16 gauge wheel base
- High limit thermal cutout safety device
- Non-Mercury tip over switch
- 2-year limited warranty



The PKB Yellow Jacket Portable Unit Heater

The King Yellow Jacket portable unit heater is constructed to hold up to the rigorous demands of a jobsite or industrial facility. It is the best heat source to assist in dry-out applications where dry electric heat is preferred to propane or kerosene space heaters. In addition, electric heat has no odor, flame or carbon monoxide. The high CFM and low temperature rise are also key features to make the Yellow Jacket the best solution for temporary large capacity heating applications.

Ordering Information

	MODEL	KW	BTUH	PHASE	VOLTS	AMPS	CFM
208V	PKB2010-1	10	34.1	1	208	48.1	825
	PKB2015-1	15	51.2	1	208	72.1	825
	PKB2010-3	10	34.1	3	208	27.7	825
	PKB2015-3	15	51.2	3	208	41.6	825
	PKB2020-3	20	68.3	3	208	55.5	1100
	PKB2030-3	30	102.4	3	208	83.3	1350
240/208V	PKB2410-1	10/7.5	34.1	1	240/208	41.6/36.1	825
	PKB2415-1	15/11.25	51.2	1	240/208	62.5/54.1	825
	PKB2410-3	10/7.25	34.1	3	240/208	24/20.8	825
	PKB2415-3	15/11.25	51.2	3	240/208	36/31.2	825
	PKB2420-3	20/15	68.3	3	240/208	48.1/41.6	1100
	PKB2430-3	30/22.5	102.4	3	240/208	72.1/62.5	1350
480V	PKB4810-1	10	34.1	1	480	20.8	825
	PKB4815-1	15	51.2	1	480	31.3	825
	PKB4810-3	10	34.1	3	480	12	825
	PKB4815-3	15	51.2	3	480	18	825
	PKB4820-3	20	68.3	3	480	24	1100
	PKB4830-3	30	102.4	3	480	36.1	1350

Specifications

Construction..... 20 gauge steel
 Elements..... Spiral Finned
 Louvers..... Adjustable
 Fan Blade..... Aluminum
 Cord Length..... 6 ft. (no plug)
 Motor..... Unit Bearing
 Approvals..... ETL (517271) & (30314521)

Minimum Clearance

front.....3 ft.
 top..... 1 ft.
 sides.....1 ft.
 rear..... 1 ft.

Options

-SB OPTIONAL 6" BASE, NO WHEELS
 -25C 25 foot cord